



ACCESS DOORS

Flush – Universal – Model UF5000

For installation in drywall, plaster, masonry or tile ceilings and walls. Features rounded safety corners, one-piece trim flange and continuous concealed hinge. 1-1/4" deep mounting frame with screwdriver-operated cam latch. Gray baked enamel finish.



No.	Dim. In.		No. Latches
	Door	Ceiling/Wall Open.	
UF5000-08	8 x 8	8-3/8 x 8-3/8	1
UF5000-12	12 x 12	12-3/8 x 12-3/8	1
UF5000-16	16 x 16	16-3/8 x 16-3/8	2
UF5000-18	18 x 18	18-3/8 x 18-3/8	2
UF5000-24	24 x 24	24-3/8 x 24-3/8	4
UF5000-2436	24 x 36	24-3/8 x 36-3/8	5




Babcock-Davis

ACCESS DOORS

General Purpose – Model WBGD

Features 18-ga. steel frame, 14-ga. steel door, concealed piano-type hinge and flush cam latches. 170° opening angle. Gray enamel finish.



No.	Dim. In.	
	Opening	Door
WBGD-1212	12-1/4 x 12-1/4	12 x 12
WBGD-1818	18-1/4 x 18-1/4	18 x 18
WBGD-2424	24-1/4 x 24-1/4	24 x 24




THOMAS ENTERPRISES

ACCESS PANELS

Model TM

Provides service access to plumbing, heating, air conditioning and electrical systems. For use in masonry, tile or wood walls. Features 14-ga. steel door, 16-ga. steel frame with 1" flange, concealed hinges and screwdriver-operated cam locks.




No.	Dim. In.		No. Latches
	Door	Wall Open.	
TM-12	12 x 12	12-3/8 x 12-3/8	1
TM-16	16 x 16	16-3/8 x 16-3/8	1
TM-18	18 x 18	18-3/8 x 18-3/8	1
TM-24	24 x 24	24-3/8 x 24-3/8	4



ACCESS DOORS

Model MIL



Flush design for installation in drywall ceilings or walls. Features double-acting spring hinges for 175° opening. 16-ga. steel outer frame allows flange to be concealed by drywall cement. Fits standard wood or steel stud spacing without need for additional braces. Powder coat finish.

No.	Stud Spacing In.*	Dim. In.	
		Opening	Door
MIL-12	12	12-1/2 x 12-1/2	12 x 12
MIL-16	16	16-1/2 x 16-1/2	16 x 16
MIL-18	18	18-1/2 x 18-1/2	18 x 18
MIL-24	24	24-1/2 x 24-1/2	24 x 24

* Center to center.



DUCT ACCESS DOORS

Models ADR1 & ADR2



For use on round duct. Features galvanized steel construction with mill finish, synthetic knobs with threaded metal inserts, and sponge gasket. Max. pressure 20" w.g.

No.	Dim. In.	Ga.	For Duct Dia. In.
ADR1-06	10 x 6	22	6
ADR1-08	10 x 6	22	8
ADR1-10	10 x 6	22	10
ADR1-12	10 x 6	22	12
ADR1-14	10 x 6	22	14
ADR1-16	10 x 6	22	16
ADR1-18	10 x 6	22	18
ADR1-20	10 x 6	22	20
ADR2-16	16 x 12	20	16
ADR2-18	16 x 12	20	18
ADR2-20	16 x 12	20	20
ADR2-22	16 x 12	20	22
ADR2-24	16 x 12	20	24