




**SPIRAL DUCT**  
Gasketed – Eastern Tight™




Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. 10-ft. length. Meets ASTM A653 and A924 specifications.

No.	Dia. In.	Ga.
6 SP6	6	28
8 SP8	8	26
10 SP10	10	26
12 SP12	12	26
14 SP14	14	26
16 SP16	16	24
18 SP18	18	24
20 SP20	20	24
22 SP22	22	24
24 SP24	24	24

**PRESSED ELBOWS**

90° – Gasketed – Eastern Tight™




Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.
6 PE90T6	6
8 PE90T8	8
10 PE90T10	10
12 PE90T12	12

**FABRICATED ELBOWS**

90° – Gasketed – Eastern Tight™




Single-wall, 5-piece design. Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.
14 E90T14	14
16 E90T16	16
18 E90T18	18
20 E90T20	20
22 E90T22	22
24 E90T24	24

**FABRICATED ELBOWS**

45° – Gasketed – Eastern Tight™




Single-wall, 3-piece design. Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.
14 E45T14	14
16 E45T16	16
18 E45T18	18
20 E45T20	20
22 E45T22	22
24 E45T24	24

**PRESSED ELBOWS**

45° – Gasketed – Eastern Tight™




Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.
6 PE45T6	6
8 PE45T8	8
10 PE45T10	10
12 PE45T12	12

**PRESSED REDUCERS**

Gasketed – Eastern Tight™



Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.		Lgth. In.
	D1	D2	
8 PRDT86	8	6	3-5/8
10 PRDT106	10	6	5-3/8
10 PRDT108	10	8	3-5/8
12 PRDT128	12	8	5-3/8
12 PRDT1210	12	10	3-5/8

**Quality Products**


**Quality People**



Eastern Sheet Metal

## PRESSED REDUCERS

Gasketed – Eastern Tight™




Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design and 30° converging angle. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.		Lgth. In.
	D1	D2	
8 PRDTB86	8	6	5-5/8
10 PRDT106	10	6	7-3/8
10 PRDT108	10	8	5-5/8
12 PRDT128	12	8	7-3/8
12 PRDT1210	12	10	5-5/8

## FABRICATED REDUCERS

Gasketed – Eastern Tight™




Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.		Lgth. In.
	D1	D2	
16 RDT1610	16	10	10
16 RDT1612	16	12	8
16 RDT1614	16	14	8
18 RDT1812	18	12	10
18 RDT1814	18	14	8
18 RDT1816	18	16	8
20 RDT2014	20	14	10
20 RDT2016	20	16	8
20 RDT2018	20	18	8
22 RDT2220	22	20	8
24 RDT2418	24	18	10
24 RDT2420	24	20	8
24 RDT2422	24	22	8

## FABRICATED REDUCERS

Gasketed – Eastern Tight™




Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.		Lgth. In.
	D1	D2	
14 RDBT148	14	8	12
14 RDBT1410	14	10	10
14 RDBT1412	14	12	10
16 RDBT1610	16	10	12
16 RDBT1612	16	12	10
16 RDBT1614	16	14	10
18 RDBT1812	18	12	12
18 RDBT1814	18	14	10
18 RDBT1816	18	16	10
20 RDBT2016	20	16	10
20 RDBT2018	20	18	10
22 RDBT2218	22	18	10
22 RDBT2220	22	20	10
24 RDBT2418	24	18	12
24 RDBT2420	24	20	10

## PRESSED TEES

Gasketed – Eastern Tight™




Assembled tee with saddle tap. Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Dia. In.		Rad. In.	Body Lgth. In.
	Inlet	Outlet		
6 PTT66	6	6	.787	16
6 PTT88	8	8	.787	18
10 PTT1010	10	10	1.00	20
12 PTT1212	12	12	1.00	22

## PRESSED TAPS

Field Installed – Gasketed – Eastern Tight™



Triple-lipped EPDM rubber gasket provides airtight seal and reduces installation time by eliminating need for joint sealing. Galvanized steel construction with single-wall design. -20°F to +212°F temperature rating. Meets ASTM A653 and A924 specifications.

No.	Inlet Dia. In.	Rad. In.	For Duct Dia. In.
6 PFTCT68	6	.787	8
6 PFTCT610	6	.787	10
6 PFTCT612	6	.787	12
6 PFTCT1406	6	.787	14
6 PFTCT1606	6	.787	16
6 PFTCT1408	8	.787	14
6 PFTCT1608	8	.787	16
8 PFTCT88	8	.787	8
8 PFTCT810	8	.787	10
8 PFTCT812	8	.787	12
8 PFTCT2008	8	.787	20
8 PFTCT2408	8	1.00	24
10 PFTCT1010	10	1.00	10
10 PFTCT1012	10	1.00	12
10 PFTCT1014	10	1.00	14
10 PFTCT1016	10	1.00	16
10 PFTCT1810	10	1.00	18
10 PFTCT1022	10	1.00	22
12 PFTCT1210	12	1.00	10
12 PFTCT1212	12	1.00	12
12 PFTCT1214	12	1.00	14
12 PFTCT1216	12	1.00	16
12 PFTCT2012	12	1.00	20
12 PFTCT2412	12	1.00	24

**We are continually adding new products. Call us with your inquiries.**