




## FAN FORCED WALL HEATERS Series 3310



Constructed of heavy gauge steel with rough-in dimensions of 19-5/16" H x 14-3/16" W x 4" D. 600 RPM motor drives vane axial blower to deliver 175 CFM downflow air. Features standard thermal overload cutoff and built-in thermostat. Temperature range 55°F to 85°F. Ivory. UL listed.

### Wall Heaters


No.	Watts	BTU	Volts	Amps
WH-E3313TRP	1500	5120	120	12.5
WH-HF3315TRP	3000/2250	10,240	240/208	12.5/10.8
WH-HF3316TRP	4000/3000	13,648	240/208	16.6/14.4

### Accessories

No.	Desc.
WH-3310EX33	Surface Mounting Frame
WH-3310FPQ	Rough In Box only

Note: Field installed.

## FAN FORCED WALL HEATERS Commercial – Series 3320



Constructed of heavy gauge steel with rough-in dimensions of 19-5/16" H x 14-3/16" W x 4" D. Grille measure 15-29/32" W x 20-27/32" H. 600 RPM motor drives vane axial blower to deliver 175 CFM downflow air. Features standard thermal overload cutoff, fan delay switch, automatic reset thermal limit switch and built-in thermostat. Temperature range 55°F to 85°F. Ivory. UL and CUL listed.


### Wall Heaters

No.	Watts	BTU	Volts	Amps
WH-F3326TTD	4000	13,800	208	19.2
WH-G3323TTD	1500	5120	277	4.1
WH-G3325TTD	3000	10,350	277	10.8
WH-G3326TTD	4000	13,800	277	14.4
WH-HF3325TTD	3000/2250	10,350/7763	240/208	12.5/10.8
WH-HF3326TTD	4000/3000	13,800/10,350	240/208	16.7/14.4

### Accessories

No.	Desc.
WH-3320EX33	4" Surface Mounting Frame, Field Installed

## CEILING HEATERS Recess-Mounted



Features "bulls-eye" venturi design for uniform air patterns in spaces with up to 12-ft. ceilings. Features enclosed steel fin sheath element, radial diffuser, propeller-style fan blades, manual reset thermal limit and 20-ga. grille. Measures 23-1/16" L x 23-1/16" W x 9-1/8" D. White powder coat finish. Includes factory installed thermostat, transformer and disconnect switch.

No.	kW	BTU	Volts AC
WH-G3484-TA1S	4.0	13,600	277

## POWER DISCONNECT SWITCHES

For field installation in unit heater.

No.	No. Poles	Amps	Volts AC
UH-DCS202	2	20	120 to 277
UH-DCS403	3	40	—
UH-DCS603	3	60	120 to 600

## THERMOSTATS Low Voltage



For gas/oil or electric systems. Features long life mercury switch. Wall mounted.

No.	Volts	Desc.
UH-MX1002	24	Heating only

## THERMOSTATS Line Voltage



SPDT design for heating or cooling applications. Measures 4.75" H x 2.8" W x 1.5" D. Features built-in bi-metal thermometer. UL and CSA listed.

No.	Setpoint Temp. Range °F		Volts AC
	Cool	Heat	
LVT-STAT	50 to 90	35 to 75	120 to 277