




CURBS PLUS INC. ROOF CURBS

Insulated



18-ga. galvanized steel construction; welded one-piece design. Features 2 x 2 pressure-treated wood nailer and 1-1/2" thick fiberglass insulation.

No.	Outside Dim. In. W x L x H
CPC-3-121212	12 x 12 x 12
CPC-3-151512	15 x 15 x 12
CPC-3-16512	16.5 x 16.5 x 12
CPC-3-171712	17 x 17 x 12
CPC-3-18512	18.5 x 18.5 x 12
CPC-3-18523	18.5 x 18.5 x 23
CPC-3-191912	19 x 19 x 12
CPC-3-22512	22.5 x 22.5 x 12
CPC-3-22521	22.5 x 22.5 x 21
CPC-3-232312	23 x 23 x 12
CPC-3-26512	26.5 x 26.5 x 12
CPC-3-272712	27 x 27 x 12
CPC-3-28512	28.5 x 28.5 x 12
CPC-3-28518	28.5 x 28.5 x 18
CPC-3-292912	29 x 29 x 12
CPC-3-34512	34.5 x 34.5 x 12
CPC-3-34518	34.5 x 34.5 x 18
CPC-3-58512	58.5 x 58.5 x 12

CURBS PLUS INC.

ROOF EQUIPMENT SUPPORTS

18-ga. galvanized steel construction; welded one-piece design. Features full-depth C-channel reinforcement and 6" spreader channels on 12" centers; 2 x 4 pressure-treated wood nailer. Galvanized counterflashing attached with tek screws and neoprene washers.




No.	Dim. L x H
CPES-3-0212	2' x 12"
CPES-3-0312	3' x 12"
CPES-3-0412	4' x 12"
CPES-3-0612	6' x 12"

LUMALIER

AIR DISINFECTORS

Ultraviolet



Installs into side of standard air duct using 3.5" diameter cutout. Features aluminum reflectors to enhance efficiency, inspection port to view lamp condition, and safety interlock switch. Measures 12.31" L x 7.25" W (including mounting plate) x 2.13" D (without lamp). 120-277V, 50-60Hz. Includes (1) PL-S L35W/TUV lamp and 9-ft. power cord with plug.

No.	Dim. In. H x D	Watts	Lamp Life Hrs.
ADPL-136	6 x 17	35	9000

DAIKIN AC HEAT PUMPS

Indoor Units – Series FTXS

For single zone applications. Features air-purification filter, flat panel design, temperature setback and power-saving Intelligent Eye. Wireless remote controller. For use with R410A refrigerant. 208/230V, 60Hz, 1 phase. **Note:** Combine with Series RX outdoor unit to form complete system.




No.	Cap. BTUH		CFM Hi/Med/Low	dB(A) Hi/Med/Low		Dim. In. H x W x D
	Cooling	Heating		Cooling	Heating	
DAI-FTXS09DVJU	8500	10,000	253-220-187	38/32/25	38/33/28	10-3/4 X 30-7/8 X 7-11/16
DAI-FTXS12DVJU	11,500	11,500	286-237-187	40/33/26	39/34/29	10-3/4 X 30-7/8 X 7-11/16
DAI-FTXS18DVJU	18,000	21,600	609-529-448	45/41/36	44/40/35	11-7/16 x 41-5/16 x 9-3/8
DAI-FTXS24DVJU	22,000	24,000	586-532-477	46/42/37	46/42/37	11-7/16 x 41-5/16 x 9-3/8

HEAT PUMPS

Outdoor Units – Series RX

For single zone applications. Compact, lightweight design. 13 SEER. HSPF 7.7. Operating range 14°F to 115°F cooling, 5°F to 64°F heating. For use with R410A refrigerant. 208/230V, 60Hz, 1 phase.

Note: Combine with Series FTXS indoor unit to form complete system. **Available in 13 or 16 SEER;** specify when ordering.



No.	Cap. BTUH	dB(A)	Max. Piping Lgth. Ft.	Max. Height Diff. Ft.	Dim. In. H x W x D
DAI-RX09FVJU	9000	50/51	66	49	21-5/8 x 30-1/8 x 11-1/4
DAI-RX12FVJU	12,000	51/53	66	49	21-5/8 x 30-1/8 x 11-1/4
DAI-RX18FVJU	18,000	53/53	98	66	28-15/16 x 32-1/2 x 11-13/16
DAI-RX24FVJU	24,000	54/54	98	66	28-15/16 x 32-1/2 x 11-13/16

Accessories

No.	Desc.
DACA-CFK-1	Conical flaring tool
DACA-FSG-1	Flare size gauge
DACA-SVA-1	5/16" to 1/4" adapter