




Twin City Fan & Blower

EXHAUST FANS

Roof Mounted – Downblast



Direct-drive centrifugal design. Features balanced fan wheel with backward-curving blades; spun aluminum housing; one-piece curb cap/inlet venturi; pillow block ball bearings; disconnect switch and galvanized birdscreen. Rubber vibration isolators protect motor, wheel and drive assembly. AMCA certified. UL and CUL listed.

No.	RPM	CFM @ .125" SP	Fan Dim. In.					Size In.	
			A	B	C	D	E	Damper	Curb
CRDD90A	–	500	21.00	19.50	2.56	15.25	17.00	10 x 10	15.5 x 15.5 x 12
CRDD160A	–	1000	30.96	27.62	4.00	24.00	24.00	18 x 18	15.5 x 15.5 x 12
DCRD060	1501	159	18.50	15.75	1.50	15.25	17.00	10 x 10	15.5 x 15.5 x 12
DCRD080	1576	312	18.50	15.75	1.50	15.25	17.00	10 x 10	15.5 x 15.5 x 12
DCRD090	1279	522	21.00	19.50	2.56	15.25	17.00	10 x 10	15.5 x 15.5 x 12
DCRD120	1109	905	27.88	20.44	3.12	22.00	20.00	14 x 14	19 x 19 x 12
DCRD120A	1503	1470	27.88	20.44	3.12	22.00	20.00	14 x 14	19 x 19 x 12



CERUS INDUSTRIAL

HVAC STARTERS

For HVAC and building control systems. Provides electronic overload, phase failure and stall protection. UL type NEMA I enclosure.



No.	AC3 Rating @ 440V	Overload Setting Amps	Motor Load (HP)		
			@ 200V AC	@ 230V AC	@ 460V AC
Enclosed – 14" L x 7" W x 5" D					
BAS1-9/J-5	9	1 to 5	1	1	3
BAS1-12/J-22	12	16 to 22	3	3	7.5
BAS1-22/J-22	22	16 to 22	3	7.5	10
BAS1-32/J-40	32	8 to 40	7.5	10	20
With Motor Circuit Protector – 21" L x 7" W x 5" D					
BAS1-9/J-G-5	9	1 to 5	1	1	3
BAS1-12/J-G-22	12	16 to 22	3	3	7.5
BAS1-22/J-G-22	22	16 to 22	3	7.5	10
BAS1-32/J-G-40	32	8 to 40	7.5	10	20

**We are continually adding new products.
Call us with your inquiries.**