




## Tyco Adhesives

### DUCT TAPE


Professional Grade



Natural rubber adhesive. 11 mils thick. Metalized. Meets UL 723 requirements.

No.	Width In.	Lgth. Yds.
DT-M	2	60

### DUCT TAPE Printed



For use on fiberglass duct systems. Dead-soft foil backing with acrylic adhesive. 4.8 mils thick. Meets UL 181 A/B requirements.

No.	Width In.	Lgth. Yds.
DT-UL	2-1/2	60

## HARDCAST GYPSUM TAPE



3" width.

No.	Lgth. Ft.
DT-5150	150
HARDCAST-DT	300



## FIRESTOP SEALANTS

NuFlex™ 814



100% silicone intumescent caulk for sealing service penetrations, expansion joints and separations in fire-rated floors and walls. Also for sealing around communication cables, insulated and PVC pipe. Expands when heated above 300°F to seal out smoke, fire, water and toxic gases. Non-sagging, UV resistant.

No.	Color	Size Fl. Oz.
FIRESTOP SEALANT	Red	10.1



## TAPER POINT SCREWS



Features 1/4" slotted hex washer head. Zinc plated. 1000 per box.

No.	Desc.
7X1/2TPM	#7 x 1/2"
10X1/2TPM	#10 x 1/2"
10X3/4TPM	#10 x 3/4"

## DRILL POINT SCREWS




Features 5/16" hex washer head, #3 point size. Zinc plated. 500 per pkg.

No.	Desc.	TPI
10X3/4DP500	#10 x 3/4"	16



## NUT SETTERS

Magnetic



Features 1/4" hex drive. Torque applied to flats; resists rounding. 50 per box.

No.	Size In.
DCD1/4	1/4
DCD5/16	5/16

## BRUSHES Duct Sealant



No.	Width In.
BRUSH	2



## PAINTS Touch-Up



No.	Color
TITUSPAINT	#26 White
TITUSPAINT-ALUM	Aluminum
TITUSPAINT-BLK	Black

**Our customer service department has the answers you need!**