



# REZNOR

## GAS-FIRED UNIT HEATERS

### V3® Series – Model UDAP



For commercial/industrial applications. Designed for 82-83% thermal efficiency. Power vented with axial fan. Features T-CORE2® heat exchanger single-burner combustion system, single-stage gas valve, direct spark ignition with lockout, pressure switch to verify vent flow, vibration isolated motor, and high-temperature limit control. Cabinet features mitered corner, less-visible hardware and gloss white finish. Can be

suspended from 2 or 4 suspension points. Low voltage terminal strip on outside for easy control wiring. Factory-installed gas line nipple. CSA certified.

**Field-installable options.** Thermostat with guard and locking cover, vertical louvers, downturn nozzle and gas conversion kits, master/slave controls for zoning, hanger kit for close ceiling mounts, stepdown transformer and manual shutoff valves.

No.	BTUH		CFM	Max. Output FPM	Dim. In. L x W x H
	Input	Output			
<b>3" Vent</b>					
REZ-UDAP-60	60,000	49,800	769	616	27 x 26-5/8 x 15-1/8
<b>4" Vent</b>					
REZ-UDAP-75	75,000	62,250	961	770	27-5/8 x 26-5/8 x 15-1/8
REZ-UDAP-100	105,000	87,150	1345	668	28-5/8 x 26-5/8 x 23-1/8
REZ-UDAP-125	120,000	99,600	1537	763	28-5/8 x 26-5/8 x 23-1/8
<b>5" Vent</b>					
REZ-UDAP-150	150,000	124,500	1921	752	42 x 38-5/16 x 20-1/8
REZ-UDAP-175	175,000	145,250	2242	877	42 x 38-5/16 x 20-1/8
REZ-UDAP-200	200,000	166,000	2562	1003	42 x 38-5/16 x 20-1/8
REZ-UDAP-250	250,000	207,500	3202	911	42 x 38-5/16 x 26-1/8

**AMERICAN METAL PRODUCTS**  
**VENT PIPE**  
Round




Galvanized steel and aluminum construction. Lightweight, double-wall design with snaplock ends.

No.	ID In.	OD In.	Lgth. Ft.
BVENT-10R24	10	11	2
BVENT-10R3	10	11	3
BVENT-4E24	4	4-1/2	2
BVENT-4E3	4	4-1/2	3
BVENT-4E5	4	4-1/2	5
BVENT-5E5	5	5-1/2	5
BVENT-6E12	6	6-1/2	1
BVENT-6E24	6	6-1/2	2
BVENT-6E3	6	6-1/2	3

No.	ID In.	OD In.	Lgth. Ft.
BVENT-6E5	6	6-1/2	5
BVENT-8R24	8	9	2
BVENT-8R3	8	9	3
BVENT-8R5	8	9	5

### VENT PIPE Adjustable Length



Designed to telescope onto standard round pipe sections.

No.	Size In.	Lgth. In.
BVENT-4E12A	4	3 to 10
BVENT-6E12A	6	3 to 10
BVENT-8R12A	8	3 to 10
BVENT-10R18A	10	3 to 16

### ELBOWS 90° – Adjustable



Adjusts from 0° to 90° to clear ceiling joists and rafters. Four-section design allows smooth bends.

No.	Dia. In.	Lgth. In. @ 0° Bend
BVENT-4EAL	4	8-3/4
BVENT-6EAL	6	10-1/4
BVENT-8RAL	8	13

### ELBOWS 45° – Adjustable

Adjusts from 0° to 45°.

No.	Dia. In.
BVENT-4E45	4
BVENT-6E45	6
BVENT-8R45	8
BVENT-10R45	10





## VENT PIPE HANGERS



Provides 1-1/2" spacing for offsets and horizontal pipe runs.

No.	For Pipe Dia. In.
BVENT-4VPH	4
BVENT-6VPH	6

## DRAFT HOOD CONNECTORS

Connects Type B gas vent pipe directly to appliance draft hood. Flexible; can be shaped to fit oval outlets.



No.	Dia. In.	Ht. In.
BVENT-4EDC	4	6.6
BVENT-5EDC	5	6
BVENT-6EDC	6	6
BVENT-8RDC	8	6
BVENT-10RDC	10	7

## VENT PIPE INCREASERS



No.	Dia. In.	Ht. In.
BVENT-5EIX6	5 x 6	6


## FIRESTOP SUPPORTS



Supports Type B gas vent pipe at appliance level. Includes support bracket.

No.	For Pipe Dia. In.	Dim. In. L x W
BVENT-4FSP	4	8-1/2 x 8-1/2
BVENT-6FSP	6	10-1/2 x 10-1/2

## SUPPORT PLATES



For supporting large size pipe sections. Also serves as firestop.

No.	For Pipe Dia. In.	Dim. In. L x W
BVENT-10RSP	10	18 x 18

## VENT COLLARS

Covers rough wall openings. For use with double-wall pipe.



No.	For Pipe Dia. In.
BVENT-4EVC	4
BVENT-6EVC	6
BVENT-8RVC	8
BVENT-10RVC	10

## STORM COLLARS



Fixed



Adjustable

Serves as counterflashing.

No.	Desc.	For Pipe Dia. In.
BVENT-4ESC	Fixed	4
BVENT-6ESC	Fixed	6
BVENT-8RSC	Adjustable	8
BVENT-10RSC	Adjustable	10

Think of Tom Barrow Co.  
for all your product needs!