



LOREN COOK COMPANY

EXHAUST VENTILATORS

Roof Mounted – Belt Drive – Model ACEB

Downblast centrifugal design with aluminum base. Includes two-piece top cap with stainless steel quick release latches, heavy-duty motor and cast iron drives. Motor, bearings and drives enclosed in weathertight compartment separated from air stream. Oil- and heat-resistant belts. Built-in lifting lugs. 115V, 60Hz, 1 phase. Includes disconnect and backdraft damper. AMCA certified; UL and CUL listed.



No.	CFM @ .25" SP	Roof Open. In.	Dim. In. W x H	HP	Curb Size In.
ACEB-70C2B	285	13-1/2 x 13-1/2	23-9/16 x 21-1/8	1/6	16-1/2 x 16-1/2
ACEB-80C3B	779	13-1/2 x 13-1/2	23-9/16 x 21-1/8	1/6	16-1/2 x 16-1/2
ACEB-100C3B	1117	13-1/2 x 13-1/2	23-9/16 x 21-1/8	1/4	16-1/2 x 16-1/2
ACEB-120C3B	1560	15-1/2 x 15-1/2	28-7/16 x 26-7/8	1/4	18-1/2 x 18-1/2
ACEB-135C3B	1800	15-1/2 x 15-1/2	28-7/16 x 27-1/4	1/4	18-1/2 x 18-1/2
ACEB-150C4B	2255	19-1/2 x 19-1/2	32-7/8 x 28-7/8	1/3	22-1/2 x 22-1/2
ACEB-150C5B	2572	19-1/2 x 19-1/2	32-7/8 x 28-7/8	1/2	22-1/2 x 22-1/2
ACEB-165C5B	2992	19-1/2 x 19-1/2	32-7/8 x 29-3/8	1/2	22-1/2 x 22-1/2
ACEB-180C5B	3234	25-1/2 x 25-1/2	37-11/16 x 34-1/2	1/2	28-1/2 x 28-1/2
ACEB-195C4B	3182	25-1/2 x 25-1/2	37-11/16 x 35	1/3	28-1/2 x 28-1/2

EXHAUST VENTILATORS

Upblast – Belt Drive

Roof mounted centrifugal design. Includes two-piece top cap with quick release latches. Motor, bearings and drives mounted on steel power assembly with solid vibration isolators and enclosed in weather-tight compartment. 1" heat shield protects motor and drive components. Aluminum wheels, heavy-duty motor, cast iron bearings, oil- and heat-resistant belts. Includes built-in lifting lugs. AMCA certified; UL and CUL listed.



Exhaust Ventilators						
No.	HP	CFM @ .75" SP	Volts	Roof Open. In.	Dim. In. W x H	Curb Size In.
VCR135V5B	1/2	1975	115	15-1/2 x 15-1/2	30-3/16 x 28-5/8	18-1/2 x 18-1/2 x 23
VCR165V6B	3/4	2975	115	19-1/2 x 19-1/2	34-11/16 x 30-3/4	22-1/2 x 22-1/2 x 21
VCR180V8B	1-1/2	3953	115	25-1/2 x 25-1/2	39-7/16 x 35-7/8	28-1/2 x 28-1/2 x 18
VCR195V7B	1	4900	115	25-1/2 x 25-1/2	39-7/16 x 36-3/8	28-1/2 x 28-1/2 x 18

Accessories

No.	Desc.	Dim. In.
GREASETERMINATR	Grease capture and containment system	4-13/16 x 6-3/4

ROOF FANS

Upblast – Belt Drive



Low profile design. Motor, bearings and drives mounted on tubular steel power assembly. Steel housing and fan blades feature polyester powder finish. Heavy-duty motor, pillow block ball bearings, oil- and heat-resistant belts and cast iron drives. 55-1/4" diameter. AMCA certified; UL and CUL listed.

No.	HP	Volts	Phases	Ht. In. Above Roof	Roof Open. In.	Curb Size In.
LXUL-48	5	480	3	50	55-1/2 x 55-1/2	56-1/2 x 56-1/2 x 12